

SILENT TYPE GENERATOR YX 20

SILENT TYPE GENERATOR YX 20



Kode Produk: YX-20

Cooling System : Closed water-cooledStarting Method : D.C 12V or 24V electric startingRated Voltage (V) : 220/380 or 230/400Rated Frequency (Hz) : 50Rated Speed (Rpm) : 1500

| | |
|------------------|-------|
| Model | YX 20 |
| Rated Power (KW) | 20 |

| Model | YX 20 |
|-------------------------------|--|
| Rated Power (KVA) | 25 |
| Rated Voltage (V) | 220/380 or 230/400 |
| Rated Frequency (Hz) | 50 |
| Engine Model | K4100D |
| Rated Output (KW) | 30.1 |
| Governing Method | mechanical |
| Bore x Stroke (mm) | 100 x 115 |
| Intake Method | Nature |
| Oil Volume (L) | 9 |
| Fuel Consumption (g/kw.h) | 246 |
| Fuel Consumption (L/Hr) | 8.6 |
| Oil Consumption (L/Hr) | 1.08 |
| Exhaust Flow (L/S) | 67.5 |
| Exhaust Temperature (celsius) | 380 |
| Water Volume (L) | 20 |
| Cooling System | Closed water-cooled |
| Starting Method | D.C 12V or 24V electric starting |
| Alternator Model | BC184E |
| Rated Power (kw) | 20 |
| Rated Voltage (V) | 220/380 or 230/400 |
| Rated Current | 38 |
| Rated Frequency (Hz) | 50 |
| Rated Speed (Rpm) | 1500 |
| Power factor Cos | 0.8 |
| Phase Connection | 3-phase |
| Winding Connection | 4 wires connected (12 wires for 3 phase) |
| Excitation Method | Brushless |
| Insulation Class | Class H |
| Voltage Regulation | Manual / Automatic |

| | |
|--|----------------------|
| Model | YX 20 |
| Control Panel | |
| Net Weight - SILENT (kg) | 800 |
| Dimension - SILENT (l x w x h) (m3) | 2.05 x 0.85 x 1.1 |
