

SILENT TYPE GENERATOR YX 30

# SILENT TYPE GENERATOR YX 30



**Kode Produk: YX-30**

Cooling System : Closed water-cooledStarting Method : D.C 12V or 24V electric startingRated Voltage (V) : 220/380 or 230/400Rated Frequency (Hz) : 50Rated Speed (Rpm) : 1500

Model	YX 30
Rated Power (KW)	30
Rated Power (KVA)	37.5

Model	YX 30
Rated Voltage (V)	220/380 or 230/400
Rated Frequency (Hz)	50
Engine Model	K4100ZD
Rated Output (KW)	42
Governing Method	mechanical
100 x 115	
Intake Method	Nature
Oil Volume (L)	9
Fuel Consumption (g/kw.h)	246
Fuel Consumption (L/Hr)	12
Oil Consumption (L/Hr)	1.05
Exhaust Flow (L/S)	101
Exhaust Temperature (celsius)	452
Water Volume (L)	20
Cooling System	Closed water-cooled
Starting Method	D.C 12V or 24V electric starting
Alternator Model	BC184H
Rated Power (kw)	30
Rated Voltage (V)	220/380 or 230/400
Rated Current	57
Rated Frequency (Hz)	50
Rated Speed (Rpm)	1500
Power factor Cos	0.8
Phase Connection	3-phase
Winding Connection	4 wires connected (12 wires for 3 phase)
Excitation Method	Brushless
Insulation Class	Class H
Voltage Regulation	Manual / Automatic
Control Panel	
Net Weight - SILENT (kg)	880
Dimension - SILENT (l x w x h) (m3)	2.25 x 0.93 x 1.17