

RICE COMBINE HARVESTER



Kode Produk: RICE COMBINE HARVESTER

RICE COMBINE HARVESTER

SPECIFICATION OF RICE COMBINE HARVESTER

Engine

Engine Model : 498BT/BZT/L, 4C6-88M22

Rated Power : 65 KW/88 HP, alternative 55 KW/75 HP

Type : Water-cooled, 4-Cylinder, DI-injection, Vertical Diesel, Turbocharged Engine

Driving System

Crawlers : 90 mm x 51 mm x 450 mm (500mm)

Minimum Ground Clearance: 280 mm

Gearbox Type : Hydraulic type + HST (3F, 3R)

Pick up Reel type : Teeth (Off-Centre), diameter 900 mm, Nos 5

Cutting Bar Length : 2,228 mm

Type of Cutting Bar : Screw Conveying

Threshing System : Spiked Tooth Axial Flow

Threshing Cylinder size : diameter 620 mm, length 1,700 mm

Vibrating Sieve : Adjustable Sieve or Round Sieve

Fan Type	: Swirl, diameter 405 mm, Nos 4
Thresher Top Cover	: Adjustable
Grain Storing	: Option 1 - Big Grain Tank with Unloading Auger, capacity 1,600 L Option 2 - Small Tank manual operation
Dimension (L x W x H)	: 5,100 mm x 2,600 mm x 2,450 mm
Weight	: 3,000 Kg
Feeding Capacity	: 4 Kg/s
Harvesting Capacity	: 0.4 - 0.75 hm ² /h
